



SHAKER VIRO | neo

»The
paint shaker
for small PoS«

smartCONNECT
READY

PRODUCT
VIDEO



- | Dispersion
- | Varnishes
- | Wood protection

Reliable

Spindle splash protection reduces significantly downtime caused by dirty drive and clamping elements in case of any paint spills.

Ease of use

Intelligent smartMIX feature can automatically choose mixing time by either pressing one button or simply by closing the door.

Economic

A paint shaker engineered to the renowned Collomix standards with affordability in mind.

MADE IN

GERMANY

 **Collomix**
.colorTEC



Features

- Intelligent smartMIX feature can automatically choose mixing time by either pressing one button or simply by closing the door.
- Unique Intelligent Clamping Control system continually monitors the clamping pressure during mixing and adjusts that pressure to ensure a perfect grip.
- Splash Guard prevents mixer downtime by protecting clamping mechanism in case of paint pollution.
- Low noise emission and smooth operation at Point-of-Sale.
- Safe and easy handling and loading of paint-containers because of a loading board.
- Door can be easily swapped from left to right-handed opening.
- All electronics are contained in one single module which can be replaced or upgraded in less than a minute.
- optional smartCONNECT gives you access to real-time data on usage and performance.

Technical data

CONTAINER	
Max. mixing weight	35 kg
Rec. continuous working weight	25 kg
Container height	50 - 400 mm
Mixing bench dimensions	370 x 360 mm
Top clamping plate dimensions	335 x 335 mm
Container type	round, oval, metal, plastic
Multiple containers at the same time	yes
PERFORMANCE	
Power supply	230 V / 50 Hz (opt. 110 V / 60 Hz)
Motor output	0.9 kW
Variable speed	no
Recommended mixed throughput	low to medium
OPERATION	
Mixing times	3 programmable times
Clamping pressure	automatic - depending on 2 selectable containers heights
Door option	manual swing door (door opening left or right)
Loading type	Push & Slide with loading ramp
Loading board height	495 mm (+ 30 mm)
Can be combined with roller conveyor	no
SHIPPING AND INSTALLATION	
Machine dimensions (W x D x H)	675 x 542 x 1169 mm
Machine weight	115 kg
Shipping dimensions (W x D x H)	800 x 620 x 1250 mm
Shipping weight	130 kg
Transport rollers	yes
Installation	adjustment-free 3-foot installation
SERVICE	
Splash guard index	Spindle cover



Collomix GmbH

Daimlerstraße 9
85080 Gaimersheim
Germany

P: +49 (0) 8458 / 32 98 0

F: +49 (0) 8458 / 32 98 30

E: info@collomix.de

www.collomix.com